



## H03VVH2-F



### Flexible PVC cable

**Max conductor temp.** : 70°C  
**Rated voltage Uo/U** : 300/300V  
**Cenelec designation, PL** : H03VVH2-F

#### Application

PVC insulated flexible cable certified for application in living and household appliances.

#### STANDARDS APPLIED

**Construction** : CENELEC HD 21.5  
 IEC 60227- 5  
**Flame retardancy** : IEC 60332-1  
**Halogen-free** : No

#### APPROVALS

<HAR>  
 CE-marking, acc. to LVD.

### CONSTRUCTION

<b>Conductor</b>		Multistranded copper
<b>Insulation</b>		PVC
<b>Outer sheath</b>		PVC
<b>Marking</b>		Marking on one of the cores
<b>Mode of packing</b>		Box or reel.

### DIMENSIONS for H03VVH2-F ( flat )

Rev.4.

No. of cores and conductor area mm <sup>2</sup>	Cond. type )	El. No.		Art. No.		Outer diameter appr. mm	Weight appr. Kg/km	Delivery length m	
		Box	Reel	Box	Reel			Box	Reel
2 x 0,75 white black	MR MR	1070161	1070171 1070170	161880	160882 161877	3,4 x 5,6 3,4 x 5,6	36 36	50	100 100

\*) MR = multi stranded round

Mode of packing and length can be changed.