



## H05 RN-F



### Drakaflex

#### Flexible rubber cable

Max cond. temperature : 60°C  
 Rated voltage, Uo/U : 300/500V  
 Cenelec designation : H05RN-F  
 A05RN-F

#### Application

Tough oil resistant rubber cable certified for indoor and outdoor use. This cable is flexible even when the temperature is very low. Fulfill requirement for cable type NMH, NMHO and RDO. Example: To portable engines, apparatus, cranes, machines, extension lead etc.

#### STANDARDS APPLIED

**Construction** : CENELEC HD 22.4  
 IEC 60245-4  
**Flame retardancy** : IEC 60332-1  
**Halogen-free** : No

#### APPROVALS

**<HAR>** for 1mm<sup>2</sup>  
**NEMKO** for 1,5 and 2,5mm<sup>2</sup>  
**CE-marking, acc. to LVD**

### CONSTRUCTION

<b>Conductor</b>		Multi stranded, tinned copper
<b>Insulation</b>		EPDM rubber
<b>Outer sheath</b>		Oil and weather resistant rubber
<b>Marking</b>		Marking on outer sheath
<b>Colour</b>		Black
<b>Mode of packing</b>		Box

### DIMENSIONS

Rev.8.

No. of cores and conductor area mm <sup>2</sup> *)	Conductor type **)	EI. No.	EAN No.	Outer diameter appr. mm	Weight appr. Kg/km	Delivery length m
3G 1	MR	1076042	7021521052166	7,3	88	100
3G 1,5	MR	1076043	7021521052302	8,9	120	75
3G 2,5	MR	1076044	7021521052456	10,5	170	50

\*) G = One of the conductors is Yellow/Green, for earth.

\*\*) MR = Multistranded round.

Mode of packing and length can be changed.