



PR Super 500V



Installation cable

Max conductor temp : 70 °C
Rated voltage Uo/U : 300/500V

Cenelec designation : N05VA5V-U (round)
: N05VA5VH2-U (oval)

STANDARDS APPLIED

Construction : NEK 535
Flame retardancy : IEC 60332-1
Halogen-free : No

APPROVALS

NEMKO
CE-marking, acc. to LVD

Application

PVC-insulated cable for fixed installasjon, for in-and outdoor use.
National regulations for electrical installation must be followed.

CONSTRUCTION

Conductor	Solid copper
Insulation	PVC
Bedding	Extruded
Metal sheath	Aluminium tape with bare earth conductor (PE)
Outer sheath	PVC
Colour	White
Marking	One conductor with marking
Mode of packing	Coil, reel, drum or box

DIMENSIONS

Rev.5

No. of cores and area mm ²	Cond.-type *)	El. No. (Art. No.)			Outer diameter appr. mm	Appr. Weight Kg/km	Delivery length m		
		Coil	Reel	Box			Coil	Reel	Box
Oval									
2 x 1,5/1,5	ER	1065953 (260500)	1065963 (260501)	1034845 (260540)	7,8 x 5,4	90	50	500	100
2 x 2,5/2,5	ER	1065954 (260510)	1065907 (260590)	1034846 (260560)	8,8 x 6,4	130	50	450	50
Round									
2 x 4/4	ER	1065955 (260520)	1065908 (260591)		10,1	210	50	200	
2 x 6/6	ER	1065956 (260530)	1065966 (260531)		11,6	300	50	250	
3 x 1,5/1,5	ER	1065957 (260503)	1065909 (260592)	1034855 (260550)	8,0	130	50	300	50
3 x 2,5/2,5	ER	1065958 (260513)	1065968 (260514)	1034856 (260570)	9,3	180	50	250	50
3 x 4/4	ER	1065959 (260524)	1065969 (260525)		11,8	310	50	200	
3 x 6/6	ER	1065960 (260534)	1065970 (260535)		13,7	410	50	150	
4 x 1,5/1,5	ER	1065961 (260506)	1065910 (260593)		9,6	170	50	250	
4 x 2,5/2,5	ER	1065962 (260516)	1065911 (260594)		10,4	215	50	200	

*)ER=Solid round

Mode of packing and length can be changed.
Not all dimensions are in stock.