



PROFIT



Conductors/cable in tube

Technical/electrical data: see datasheet for actual cable

Application

Conductors and cable prefabricated in tubes, 16mm or 20mm. Certified for house-wiring, allowed for all building constructions.

Flexible even when the temperature is very low, down to -25°C.

National regulations for electrical installation must be followed.

STANDARDS APPLIED

See data sheet for actual cable

APPROVALS

See data sheet for actual cable

CONSTRUCTION

Tube	Corrugated tube, black self-quenching Polypropylene. 16 and 20mm.
Conductor/Cable	See table below
Marking	Printed on the insulation/sheath
Mode of packing	Coil

DIMENSIONS

Rev.5.

No. of cores and conductor area mm ² *)	EAN No.	EI.No.	Diameter tube mm	Weight incl. tube appr. Kg/km	Delivery length m
PROFIT PN 3G1,5mm ²	6410004123027	1050160	16	111	B100
PROFIT PN 3G2,5mm ²	6410004123041	1050161	16	147	B100
PROFIT PN 3G4mm ²	6410004017340	1050162	20	198	B50
PROFIT PN 3G6mm ²	7021521726500	1050167	20	275	B50
PROFIT PN 4G1,5mm ²	6410004123065	1050163	16	133	B100
PROFIT PN 4G2,5mm ²	6410004017425	1050164	20	186	B50
PROFIT PN 5G1,5mm ²	6410004123089	1050165	20	160	B50
PROFIT PN 5G2,5mm ²	6410004123102	1050166	20	218	B50
PROFIT PR 2x1,5 ER/1,5	7021522605842	1050172	20	153	B50
PROFIT PR 2x2,5 ER/2,5	7021522605859	1050173	20	193	B50
PROFIT PR 3x1,5 ER/1,5	7021522605866	1050174	20	185	B50
PROFIT PR 3x2,5 ER/2,5	7021522605873	1050175	20	240	B50
PROFIT CAT.6 UTP 4p	7021521062202	1050176	16	80	B100
PROFIT Koaks 75ohm	7021521062615	1050179	16	102	B100
PROFIT PVXP 2x1/1mmØ	7021522618781	1050178	16	108	B100
PROFIT TP90 2x1,5 FR	7021521003151	1050183	16	105	B100
PROFIT Snurrebukk (stand)	7021522500055	8817115			stk.

*) G = one conductor is Yellow/green