



Connection wire

RK 500V

Multi stranded

Max conductor temp. : 70°C

Rated voltage, Uo/U : 300/500V

Cenelec designation : H05V-K

STANDARDS APPLIED

Construction : CENELEC HD 21.3
IEC 60227-3

Flame retardancy : Ja, IEC 60332-1

Halogen-free : Nei

APPROVALS

<HAR>

NEMKO

CE-marking, acc. to LVD

Application

Flexible PVC insulated wire certified for house-wiring in conduits and as connection wire.

National regulations for electrical installation must be followed.

CONSTRUCTION

Conductor		Multi-stranded copper
Insulation		PVC
Marking		Printed on the insulation
Mode of packing		Coil or drum. Can also be delivered as "Boxed wire".

DIMENSIONS

Rev.2.

Conductor area mm ²	Art. No.	Conductor type *)	El. No. Coil	Outer diameter appr. mm	Weight appr. Kg/km	Delivery length coil m
0,5	black	MR	1050500	2,2	9	100
	white		1050501	2,2	9	100
	blue		1050504	2,2	9	100
	brown		1050509	2,2	9	100
	red		1050502	2,2	9	100
	yellow/green		1050506	2,2	9	100
0,75	black	MR	1050510	2,3	12	100
	white		1050511	2,3	12	100
	blue		1050514	2,3	12	100
	brown		1050519	2,3	12	100
	red		1050512	2,3	12	100
	grey		1050517	2,3	12	100
	green		1050503	2,3	12	100
	yellow		1050505	2,3	12	100
	yellow/green		1050516	2,3	12	100
	1,0		black	MR	1050520	2,5
white		1050521	2,5		14	100
blue		1050524	2,5		14	100
brown		1050529	2,5		14	100
red		1050522	2,5		14	100
grey		1050527	2,5		14	100
yellow/green		1050526	2,5		14	100

*) MR = multi stranded round

Mode of packing and length can be changed.
Not all dimensions are in stock.



Draka Norsk Kabel