




## UC900 SS23 Cat.7

### S/FTP



### Application

Primary (Campus), Secondary (Riser), Tertiary (Horizontal)  
IEEE 802.3: 10Base-T; 100Base-T; 1000Base-T; 10GBase-T  
IEEE 802.5 16 MB; ISDN; TPDDI; ATM

### Standards

EN 50173-1; EN 50288-4-1  
ISO/IEC 11801; IEC 61156-5

### Flame resistance

LSHF(LSOH): IEC 60332-1; IEC 60754-2; IEC 61034  
LSHF-FR(LSFROH): additionally IEC 60332-3-24

### Construction

Conductor	bare copper wire, Ø 0.56 mm (AWG 23)
Insulation	foamskin PE, Ø 1.4 mm
Twisting	2 cores to the pair
Pair screen	Al-laminated plastic foil
Cable lay up	4 pairs (PiMF) to the core
Screen	copper braid, tinned
Sheath	LSHF or LSHF-FR orange RAL 2003



## UC900 SS23 Cat.7

### Mechanical properties

Bending radius	During operation	4 x Outer diameter
	During installation	8 x Outer diameter
Temperature range	During operation	-20°C to + 60°C
	During installation	0°C to + 50°C
Maximum tensile load	During operation	-
	During installation	100 N

### Electrical properties

at 20°C± 5°C

Loop resistance		≤ 150 Ω/km
Resistance unbalance		≤ 2%
Insulation resistance	(500 V)	≥ 5000 MΩ*km
Mutual capacitance	at 800 Hz	Nom. 43 nF/km
Capacitance unbalance	(pair/ground)	≤ 1500 pF/km
Characteristic impedance	(1-100 MHz)	(100 ± 5) Ω
	(100 - 250) MHz	(100 ± 10) Ω
	(250 - 600) MHz	(100 ± 15) Ω
Nominal velocity of propagation		ca. 79 %
Propagation delay		≤ 425 ns/100m
Delay skew		≤ 9 ns/100m
Test voltage	(DC, 1 min) core/core and core/screen	1000 V
Transfer impedance	at 1 MHz	≤ 5 mΩ/m
	at 10 MHz	≤ 5 mΩ/m
	at 30 MHz	≤ 10 mΩ/m
	at 100MHz	≤ 20 mΩ/m

### Electrical data (nominal)

(at 20°C)

F (MHZ)	Attenuation (dB/100m)	NEXT (dB)	PS-NEXT (dB)	ACR (dB/100m)	PS-ACR (dB/100m)	ELFEXT (dB/100m)	PS-ELFEXT (dB/100m)	Return loss (dB)
1.0	1.8	100	97	98	95	105	105	-
4.0	3.4	100	97	97	94	105	102	27
10.0	5.4	100	97	95	92	97	94	30
16.0	6.8	100	97	93	90	93	90	30
20.0	7.7	100	97	92	89	91	88	30
31.2	9.6	100	97	90	87	87	84	30
62.5	13.7	100	97	86	83	81	78	30
100.0	17.4	100	97	83	80	77	74	30
125.0	19.5	95	92	75	72	75	72	26
155.5	21.9	94	91	72	69	73	70	26
175.0	23.3	93	90	70	67	72	69	25
200.0	25.0	92	89	67	64	71	68	25
250.0	28.1	90	87	62	59	69	66	24
300.0	30.9	89	86	58	55	67	64	24
450.0	38.3	87	84	48	45	64	61	23
600.0	44.8	85	82	40	37	61	58	22
750.0	52.0	83	80	31	28	59	56	21
900.0	59.4	82	79	23	20	58	55	20



## UC900 SS23 Cat.7

### Technical Data

Product name	Type	Colour	Outer diameter mm	Fire load MJ/km	Weight kg/km	Delivery form	Material code	DCN no.	El. no
UC900 SS23 4P LSHF	S/FTP	Orange RAL2003	7,5	585	55	-	1001032	-	-
UC900 SS23 4P LSHF-FR	S/FTP	Orange RAL2003	7,5	1170	55	-	1001033	-	-
UC900 SS23 2x4P LSHF	S/FTP	Orange RAL2003	7,5 x 15,0	585	110	-	1001034	-	-
UC900 SS23 2x4P LSHF-FR	S/FTP	Orange RAL2003	7,5 x 15,0	1170	110	-	1001035	-	-